恒河材料科技股份有限公司

HENGHE MATERIALS & SCIENCE TECHNOLOGY CO.,LTD

Add:No.3511 Yuejintang Road,Ningbo Petrochemical Zone,Ningbo,China.315000

Tel:0086-574-86680024 Fax:0086-574-86680088

www.hh-sh.com Email:amy@hh-sh.com

TECHNICAL DATA SHEET

C9 PETROLEUM RESIN PR-120(PA-120)TM

DESCRIPTION

C9 PETROLEUM RESIN PR-120TM is a kind of polymers, it has the properties of good heat stability,intersolubility,viscidity,light stability, it's designed for Paints,rubber,Adhesive,Printing ink industries.

PERFORMANCE PROPERTIES

Properties	Typical Value	Test Method
Apperance	Yellowish transparent granule	VISUAL TEST
Softenning Point(Ring& Ball,C)	110-120	ASTM E28
Color (Ga#)	10 Max	ASTM D1544
Acid Value (KOHmg/g)	0.30 Max	ASTMD 974
Ash（%）	0.05 Max	ASTM 5040

PACKING,STORING, TANSPORTING:

Granules in multi-ply HDPE inner bags of 25kgs net weight. To be stored in cool and dry area and keep away from heat and flame.

The information given above is based on our experience and laboratory test. It is given without warranty.

The customer must make his own trials to ensure that glue meets his requirements.